



SPECIFICATIONS

Current Rating: 10A AC/DC
 Voltage Rating: 300V AC/DC
 Housing: 54oz, UL94V-0, Black
 Contact: C1100R-1/2H
 Contact Plating: Gold Flash, over 30u" Nickel
 Strain Relief: PVC, Black
 Protection Rating: IP68

Item	Name	Finish
1	Housing	PPO, 54OZ, UL94V-0, Black
2	Strain Relief	PVC, UL94V-0, Black
3	Contact	Copper Alloy, Gold Flash on Contact over Nickel
4	Cable	UL2464, 24AWG X 4C OD=6.0mm, Color: Red, Black, Green, Blue Jack=PVC, Black

Series	Type	Pins	Style	Plating
CWP	M13-A100	XX	XX	XX
Waterproof Connector	M13 Connector A100 Style	02,03,04	MP=Male Panel Mount FP=Female Panel Mount MW=Male Wire Mount FW=Female Wire Mount MWM=Male Overmolded FWM=Female Overmolded	GD=Gold TN=Tin

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/12/12
				Checked	Lizzy	01/12/12
				Drawn	Tina	01/12/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CWP-M13-A100-04-MXX-XX**

Description: Male Type 4P A 100 Style for UL 2464 24 AWG X 4C Snap In Insert Molding Type Waterproof Connector