



SPECIFICATIONS
 Current Rating: 7A AC/DC
 Voltage Rating: 250V AC Max.
 Housing Material: UL94V-2 Nylon 6/6 Natural
 Contact Resistance: 10mΩ max., 20mΩ max after testing
 Insulation Resistance: 5000 MΩ min.
 Withstanding Voltage: 1500V AC/minute
 PC Board Thickness: .063"
 Temperature Range: -40C ~ +105C

Dimensions mm					
Pin	A	B	Pin	A	B
02	10.16	5.08	12	60.96	55.88
03	15.24	10.16	13	66.04	60.96
04	20.32	15.24	14	71.12	66.04
05	25.40	20.32	15	76.20	71.12
06	30.48	25.40	16	81.28	76.20
07	35.56	30.48	17	86.36	81.28
08	40.64	35.56	18	91.44	86.36
09	45.72	40.64	19	96.52	91.44
10	50.80	45.72	20	101.6	96.52
11	55.88	50.80			

Series	Pitch	Type	Mounting	Positions	Color	Plating
DBHR	X	X	X	XX	XX	XX
DBHR receptacle with board hooks	1=.100" 2=.156" 3=.200"	T=Top S=Side B=Bottom	Blank=None H=Hook R=Locking Ramp HR=Hook & Ramp	2-25	BK=Black WT=White	TN=Tin GD=Gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/24/03
				Checked	Lizzy	03/24/03
				Drawn	Tina	03/24/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DBHR-3-T-H-XX-XX-XX**

Description: PC board connector, 3.96mm pitch