



Dimensions					
Positions	A	B	C	D	E
09	31.00	47.00	15.60	15.80	24.99
15	40.00	48.00	15.80	15.80	33.32
25	53.50	48.00	16.00	16.00	47.04
37	69.20	48.60	16.00	20.80	
50	67.00	48.40	19.00	24.00	

Positions	Cable Entry Diameter (mm) U Type				
9	6	7	8	9.5	
15	7	9	10.5		
25	8	9	10	11	13
37	9	10	11.5	13.5	15.5
50	10	13	14	16	18

Positions	Cable Entry Diameter (mm) V Type									
9	5.5	6	6.5	7	7.5	8	8.5	9	9.5	
15	6	7	8	9	10	12				
25	7	8	9	10	12	13	14.5			
37			10	12	14	16				
50		10	13	14.5	16	18				

↑ Standard

↑ Standard

Series	Material/Color	Style	Cable Entry	Screw	Options
DBSXX	XX	X	XX	XX	XX
09, 15, 25, 37, 50	ZM=Zinc diecast PG=Plastic gray PB=Plastic black PT=Plastic tan AM=Aluminum diecast metal PC=Plastic chrome plated	[blank]=V (oval entry) U=U style (round entry) E=Ethernet R=Right-angle	[blank]=Standard 06, 07, 08, 09, 10, 12, 13, 14, 16, 18 (See cable entry chart) GT=With Grommet Tree	SS=Standard screw TS=Metal thumb screw PS=Plastic thumb screw	[blank]=None SNP=Snap together (plastic only)

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DBSXX-ZM-X-XX-XX-XX**

Description: Metal D-sub backshell