



| | |
|-----------|---|
| SCHEMATIC | |
| MODEL NO. | A |
| SCHEMATIC | |
| MODEL NO. | B |

SPECIFICATIONS
 Contact resistance: 30 milliohms max.
 Insulation resistance: 100 megohms min.
 Withstanding: 500VAC for 1 min.

Pin Hole Jack
(Jack Bottom View)

| Item | Name | Material | Finish |
|------|----------------|-----------------------|--------|
| 1 | Pin terminal | 0.4T brass | Silver |
| 2 | Sleeve spring | 0.25T phosphor bronze | Silver |
| 3 | Break terminal | 0.4T brass | Silver |
| 4 | Pin (∅1.3) | Copper | Nickel |
| 5 | Housing | PBT+15% glass fiber | Black |
| 6 | Cover | PBT | Black |

| Series | Style | Pin Size | Circuit | Terminal Plating | Options |
|---------------|----------------------|----------|--------------------------------------|------------------|---|
| DCJ | 03 | D | X | S | X |
| DC power jack | Side entry w/ switch | D=1.3mm | A=Normally closed B=Normally open | S=Silver (std) | F=Flat tail K=Kinked tail P=Press fit |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | | UNIT: mm | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DCJ-03-D-X-S-X**

Description: DC power jack