



SCHEMATIC	
MODEL NO.	A
SCHEMATIC	
MODEL NO.	B

**SPECIFICATIONS**  
 Contact resistance: 30 milliohms max.  
 Insulation resistance: 100 megohms min.  
 Withstanding: 500VAC for 1 min.

Pin Hole Jack  
(Jack Bottom View)

Item	Name	Material	Finish
1	Pin terminal	0.4T brass	Silver
2	Sleeve spring	0.25T phosphor bronze	Silver
3	Break terminal	0.4T brass	Silver
4	Pin (∅1.3)	Copper	Nickel
5	Housing	PBT+15% glass fiber	Black
6	Cover	PBT	Black

Series	Style	Pin Size	Circuit	Terminal Plating	Options
DCJ	D420	D	X	S	X
DC power jack	Side entry w/ switch	D=1.3mm	A=Normally closed B=Normally open	S=Silver (std)	F=Flat tail K=Kinked tail P=Press fit

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DCJ-D420-D-X-S-X**

Description: DC power jack