



SPECIFICATIONS

Current rating:	1A
Voltage rating:	250 VAC
Insulation res.:	1000 MOhm min.
Contacts:	Copper alloy
Contact res.:	30 mohm max.
Withstanding:	500 VAC/1 min
Housing:	Nylon, UL94V-0
Operating temp.:	-25°C to +105°C
Processing temp:	260±5°C/5 sec

TOP VIEW
PCB LAYOUT RECOMMENDED

Series	Type	Contacts	Material	Plating
SIMM	1925X	144	X	SGXX
Single in line socket	Vertical With Latch X: S=Standard key R=Reverse key	144 contacts	A=Nylon66 B=Nylon46	SG=Selective Gold XX=Flash if blank, 6, 30µ"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/08/2012
				Checked	Lizzy	03/08/2012
				Drawn	Tina	03/08/2012
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DIMM-1925X-144-X-XX**

Description: SIMM socket with latch and centering post