



SPECIFICATIONS

Voltage Rating:	40 VAC max
Current Rating:	0.5 Ampere per contact
Contact Resistance:	30 mΩ max
Insulation Resistance:	100 MΩ min.
Body:	LCP, UL94V-0, Black
Shield:	Brass
Shield Plating:	Nickel
Contact:	Brass
Contact Plating:	Tin on Solder Tail Gold over Nickel on Contact
Withstanding:	500 VDC
Operating Temp:	-20C to +85C

Pin No.	Signal Type	Pin No.	Signal Type
1	In	11	GND
2	GND	12	In
3	In	13	CONFIG(see note 1)
4	In	14	CONFIG(see note 1)
5	GND	15	I/O
6	In	16	GND
7	In	17	I/O
8	GND	18	Out
9	In	19	RTN
10	In	20	Power Out(see note 2)

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/29/08
				Checked	Lizzy	03/29/08
				Drawn	Tina	03/29/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DPC-20F6L1BU3**
 Description: Displayport Female DIP 90° With DIP Shell Foot & Harpoon & Post & Curl