



SPECIFICATIONS
 Current Rating: 0.5A min
 Voltage Rating: 40V AC
 Withstanding: 500 VAC for 1 minute
 Insulation Resistance: 100 megaohms min.
 Contact Resistance: 30 milliohms max.

Item	Name	Material
1	Shell	Stainless Steel
2	M1 Contact	Copper Alloy
3	Housing	High Temp Plastic
4	Bottom Housing	High Temp Plastic
5	M2 Contact	Copper Alloy

Series	Gender	Position	Contact Plating	Shell Plating	Color
DPC-M	XXX	20	XX	XX	XX
Mini Display Port Connector	RF=RA, Female, Thru Hole	20=20 Positions	GDXX=Gold XX=Flash if Blank, 15, 30 u"	G=Gold N=Nickel	BK=Black WT=White

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/15/11
				Checked	Lizzy	07/15/11
				Drawn	Tina	07/15/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DPC-M-RF-20-GDXX-X-BK**

Description: Mini DP Receptacle Type