


SPECIFICATIONS

Current rating:	0.5 amps
Contact material:	Phosphor bronze
Contact resistance:	20 milliohms max.
Insulator material:	Polyester LCP, UL94V-0
Insulation resistance:	500 megohms min.
Withstanding:	200VAC for 1 min.
Operating temperature:	-40°C to +105°C
Processing temperature:	230°C for 30~60 sec. max.

RECOMMENDED P.C.BOARD LAYOUT
(Tolerance: ±0.05)

Series	Rows	Pins	Type	Pin length	Plating
DPH	2	XX	XX	SD	XX
Pin header, 1.00mm pitch	2= Dual rows	2-40 pins	[blank]=Straight RA=Right angle SM=Surface mount	SD=Standard CSL=Custom	GD=Gold SG=Selective gold TN=Tin

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/18/06
				Checked	Lizzy	08/18/06
				Drawn	Tina	08/18/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DPH-2-XX-SM-SD-XX-XX**

Description: Pin header, 1.00mm pitch, single row SMT type, base 1.00mm height