


SPECIFICATIONS

Current rating:	0.5 amps
Contact material:	Phosphor bronze
Contact resistance:	40 milliohms max.
Insulator material:	Polyester LCP, UL94V-0
Insulation resistance:	500 megohms min.
Withstanding:	200VAC
Operating temperature:	-40°C to +105°C
Processing temperature:	230C for 30-60 sec. max.

RoHS compliant

Series	Rows	Pins	Contact plating	Options
DRS	XX	XX	XX	XX
Female header	02=2 rows	02-40 positions	GD=Gold flash SG=Selective gold TN=Tin	[blank]=None TR=Tape & reel PPL=Pick and place cap

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/18/06
				Checked	Lizzy	08/18/06
				Drawn	Tina	08/18/06
				0.0 ± 0.35	0.00 ± 0.20	Angles $\pm 3^\circ$
				 UNIT: mm		


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DRS-02-XX-XX-XX**
 Description: Female header, 1.00mm pitch, dual rows SMT type, base 2.10mm height