



SPECIFICATIONS

Voltage Rating: 250VAC Max.
 Current Rating: 3 Amps Max.
 Contact Material: Copper Alloy, Nickel Plating
 Contact Resistance: 15 Mohms Max.
 Insulator Material: Thermal Plastic UL94V-0
 Withstanding: 1000 VAC/minute
 Operating Temp: -55°C to +105°C

Series	Type	Shell	Mounting face	Options
DSXX	XFC	X	XX	XX
D-Sub connector XX=Pins 09, 15, 25, 37,50	MFC=Male plug FFC=Female socket	M=Metal P=Plastic	01=.130" thru hole 02=#4-40 threaded inserts	[blank]=None GDXX=Gold Plating, (XX=Flash if blank, 5, 10, 15, 30u") BL=Blue insulator GY=Gray insulator

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DS50-FFC-M-02**

Description: D-Sub I.D.C for Plastic Female