



SPECIFICATIONS

- Current rating: 3 amps
- Contact material: Brass
- Contact resistance: 25 milliohms max.
- Insulator material: PBT, 30% glass filled, UL94V-0
- Insulation resistance: 5,000 megohms min. 500VDC
- Shell material: Steel
- Withstanding: 1,000VAC for 1 min.
- Insertion force: 300gf max.
- Extraction force: 25gf min.

Series	Gender	Port Spacing	Mounting Face Options	Options
DSDXX/YY	XX	X	X	XX
Dual-port D-sub XX=Upper position YY=Lower position (Omit if same as upper)	MM=Male over male MF=Male over female FM=Female over male FF=Female over female FMF=Female over male-female	A=.625" B=.750" C=.900"	01=.120" thru hole 02=#4-40 threaded hole 03=#4-40 threaded insert w/jackscrew 04=Boardlocks, front and rear 04S=Boardlocks, rear only 04F=Boardlocks, front only	[blank]=None FF=Ferrite filter 30GD=30µ" gold plate 15GD=15µ" gold plate

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DSD25/09HD15-FMF-B-0204**

Description: D-subminiature connector, stacked, right angle, PCB mount