



**SPECIFICATIONS**

Current rating:	3 amps
Contact material:	Brass
Contact resistance:	25 milliohms max.
Insulation material:	PBT, UL 94V-0
Insulation resistance:	5,000 megohms min at 500VDC
Shell material:	Steel
Insertion Force:	300gfMax
Separation Force:	25gf Min
Withstanding:	1,000VRMS for 1 min.
Operating temperature:	-55°C to +105°C

Dimensions			
Contacts	A	B	B
9	16.92	24.99	30.85
15	24.66	33.32	39.14
25	38.38	47.04	53.04
37	54.84	63.50	69.32

Dimensions		
Plug Spacing	E	F
0.625	15.88	28.38
0.75	19.05	31.55

Series	Gender	Port Spacing	Mounting Face	Options
DSDXX/YY	XX	X	X	XX
Dual-port D-sub XX=Upper position YY=Lower position (Omit YY if same as upper)	MM=Male over male MF=Male over female FM=Female over male FF=Female over female FMF=Female over male-female	A=.625" B=.750" C=.900"	01=.120" thru hole 02=#4-40 threaded hole 03=#4-40 threaded insert w/jackscrew 04=Boardlocks, front and rear 04S=Boardlocks, rear only 04F=Boardlocks, front only	[blank]=None FF=Ferrite filter 30GD=30μ" gold plate 15GD=15μ" gold plate

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/03/04
				Checked	Lizzy	02/03/04
				Drawn	Tina	02/03/04
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DSDXX-FF-X-0204**  
 Description: Dual Port D-subminiature connector, Female over Female