



SPECIFICATIONS

Current Rating: 15 Amp
 Insulation Resistance: 5000 Megohms Minimum
 Contact Resistance: 8 Milliohms Max
 (low level) 32 Milliohms max
 Magnetic Permeability: 2u Max
 Shock: 50g
 Vibration: 20g
 Mating Force: 150 Ounces Max
 Durability: 500 Mating Cycles Minimum
 Connector Shell: Aluminum Alloy, Nickel Plating
 Insulator: PBT (LCP Available)
 Withstanding: 600 VAC Sea Level
 Operating Temp: -55C to +150C
 Salt Spray: 48 Hours

Series	Gender	Mounting Options
DSMXX	XT	XXX
D-sub connector XX=Pins	MT=Male FT=Female	[blank]=.120" through holes RCN=Riveted clinch nuts #4-40 RJS=Riveted jackscrews #4-40

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/29/09
				Checked	Lizzy	09/29/09
				Drawn	Tina	09/29/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DSM15-FT-A**

Description: Micro D-subminiature crimp connector, female