



Dimensions			
Pos.	A	B	C
09	30.80	24.99	16.30
15	39.15	33.32	24.65
25	53.00	47.04	38.40
37	69.30	63.50	54.80
50	67.00	61.00	52.80

Series	Type	Tail options	Face options	Other options
DSXX	XX	X	XXX	XX
D-sub connector XX=Pins 9, 15, 25, 37, 50	FT=Female vertical mount MT=Male vertical mount MHT=Male high profile FHT=Female high profile	A=Standard for .052" to .125" PCB B=Wire wrap	[blank]=.120" thru hole RCN=Clinch nut RJS=Jackscrew RSB=Standoff with board locks RSB-JS=RSB with Jack Screw	[blank]=None FF=Ferrite filter YC=Yellow chromate shell

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/17/03
				Checked	Lizzy	10/17/03
				Drawn	Tina	10/17/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DSXX-FT-A-RSB-JS**

Description: D-subminiature connector, PCB straight type, stamped pin, female, boardlocks