



SPECIFICATIONS

Contact Material:	Phosphor Bronze, Gold Over Nickel Plating
Contact Resistance:	15mΩ Max. Mated
Insulation Material:	P.B.T. +30% G.F UL94V-0
Insulation Resistance:	1000MΩ at 500 VDC
Wire Size:	AWG 26 ~ 28
Operating Temp:	-55°C ~ 105°C

Dimensions (mm)					
Pos.	A	B	D	E	F
9	30.89	24.99	10.16	16.33	21.78
15	39.14	33.32	17.78	24.66	29.62
37	69.39	63.50	45.72	54.84	59.92

ECIFICATION :

STRAIN RELIEF

Series	Type	Shell	Mounting face	Color	Options
DSXX	MFC2	X	XX	XX	XX
D-Sub connector XX=Pins 09, 15, 25, 37	MFC2=Male plug Flat Cable FFC2=Female socket Flat Cable	M=Metal P=Plastic	01=Standard Through Hole 02=With 4#-40 UNC Threaded Insert	BL=Blue GY=Grey BK=Black	GDXX XX=Flash if blank, 5,10,15,20, 30μ" gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DSXX-MFC2-X-XX-XX-XX**

Description: IDC D-Sub Connector, Flat Cable Type