



SPECIFICATIONS

Current Rating: 1.5A
 Voltage Rating: 125VAC/DC
 Housing: PBT + GF, UL 94V-0, black
 Contacts: Brass
 Shell: Steel
 Contact Res: 50milliohm max
 Insulation Res: 500megohm min
 Withstanding: 500VAC/ 1 min
 Operating Temp: -25°C to +85°C
 Processing Temp:

Series	Type	Style	Version	Housing	Shell	Shell Plating	Contacts	Contact Plating	Color
CUSB	A	EM205	1M4RST	P	S	N	B	SG	BK
USB Connector	Type A	See Drawing	Single Port male 4 Contacts, Side Entry SMT plus Through Hole	P=PBT	S=Steel B=Brass	N=Nickel (std) G=Gold T=Tin	B=Brass	SG=Selective Gold	BK=Black

RoHS Compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/23/16
				Checked	Lizzy	11/23/16
				Drawn	Tina	11/23/16
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-EM205-1M4RST-P-SN-BSG-BK**

Description: USB type A male shielded SMT plus through hole mounting