


SPECIFICATIONS

| | |
|------------------------|------------------------|
| Voltage rating: | 30VAC |
| Current rating: | 1 amp |
| Contact material: | Copper alloy |
| Contact resistance: | 30 milliohms max. |
| Housing material : | Thermoplastic, UL94V-0 |
| Insulation resistance: | 1000 megohms min. |
| Shell material: | Copper alloy |
| Withstanding: | 500VAC for 1 min. |
| Temperature range: | -40°C to +105°C |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|---|-------------|-------------|
| | | | | Approved | Howard | 06/20/06 |
| | | | | Checked | Lizzy | 06/20/06 |
| | | | | Drawn | Tina | 06/20/06 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | |  | | UNIT: mm |



Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-B-04FG1AT2**

Description: USB 2.0, Type B, 4 pin female, vertical PCB mount , black insulator color