



SPECIFICATIONS

Current Rating: 1.8A pin 1&5;1A pin 2-4
 Housing: Hi Temp Thermoplastic+gf UL 94V-0
 Contacts: Copper Alloy, t=0.20mm
 Shell: Copper Alloy, t=0.20mm
 Contact Res: 30mΩ max
 Insulation Res: 100MΩ min
 Withstanding: 100VAC/1 min
 Mate Force: 3.57Kgf max
 Extract Force: 1.0 Kgf min
 Operating Temp: -30°C to +80°C



Series	Type	Style	Version	Shell	Shell Plating	Contacts	Contact Plating	Package
CUSB	UB	SAZYB	1F5RS	B	N	B	SG	TR
USB Connector	UB=Micro B	See Drawing	Single Port Female 5 Contacts, Side Entry SMT	Copper Alloy	N=Nickel (std)	B=Brass	SG=Selective Gold	TR=Tape & Reel

RoHS Compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/07/14
				Checked	Lizzy	06/07/14
				Drawn	Tina	06/07/14
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-UB-SAZYB-1F5RS-BNB-SG-TR**

Description: USB type micro B, female, shielded, SMT mounting