



SPECIFICATIONS

Current Rating: See Chart
 Voltage Rating: 600V RMS
 Insulation Resistance: 1000MΩ/500V min.
 Withstanding: 1500V AC/1-minute
 Operating Temp: -40°C ~ +105°C

Current Rating (A)				
Circuits AWG	2,3	4-6	7-10	11,12
16	9	8	7	6
18	9	8	7	6
20	7	6	5	5
22	5	4	4	4
24	4	3	3	3
26	3	2	2	2
28	2	1	1	1

Dimensions (mm)							
Circuits	A	B	C	Circuits	A	B	C
2	4.2	9.6	15.0	8	29.4	30.6	40.2
3	8.4	13.8	19.2	9	33.6	34.8	44.4
4	12.6	19.0	23.4	10	37.8	39.0	48.6
5	16.8	18.0	27.6	11	42.0	43.2	52.8
6	21.0	22.2	31.8	12	46.2	47.4	57.0
7	25.2	26.4	36.0				

Series	Type	Positions	Options
JS-A	9358	XXS	X
Connectors	High Current High Density Housing	XX=02-12 S=Single row	E=Mounting Ears Blank=No Ears

RoHS Compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Drawn	Tina	07/01/03
				Checked	Lizzy	07/01/03
				Approved	Howard	07/01/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				Unit: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-A-9358-XXS-E**

Description: 4.2mm single row plug housing