



**SPECIFICATIONS**

Current Rating: 3A AC/DC  
 Voltage Rating: 250V AC/DC  
 Contact Resistance: 10milliohms max  
 Housing: Nylon 66, UL 94V-0  
 Insulation Resistance: 1000mEGOHMS MIN  
 Withstanding: 800V AC/1-min  
 Operating Temp: -25°C to +85°C

Dimensions (mm)		
Pos.	A	B
2	2.50	7.00
3	5.00	9.50
4	7.50	12.00
5	10.00	14.50
6	12.50	17.00
7	15.00	19.50
8	17.50	22.00
9	20.00	24.50
10	22.50	27.00
11	25.00	29.50
12	27.50	32.00
13	30.00	34.50
14	32.50	37.00
15	35.00	39.50

Series	Type	Positions
JS-OE	2500VF	XX
Pluggable connectors	2.5mm female wire mount housing	02-15

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/11/05
				Checked	Lizzy	03/11/05
				Drawn	Tina	03/11/05
				$0.0 \pm 0.35$	$0.00 \pm 0.20$	Angles $\pm 3'$
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-OE-2500VF-XX**

Description: 2.5mm wire to bopard housing

G

G