

SPECIFICATIONS
Electrical Rating: 10A 125-250VAC
Contacts: Silver Alloy
Contact Resistance: <20mΩ
Actuator: PC/PA66
Housing: PA66, UL 94V-2
Insulation Resistance: >1000MΩ
Terminals: Brass, Silver Plated
Spring: SWC
Movable Arm: C2680
Bracket: PA66
Withstanding: >1500V 1 minute
Mechanical Life: 30000 cycles min.
Electrical Life: 10000 cycles min.
Temperature rise: Max. 30C
Processing Temp: 350C/3sec

Code	Color
BK	Black
WT	White
RD	Red
LYL	Yellow*
LGN	Green*
LRD	Red*

*Illuminated

Series	Type	Version	Lamp Voltage	Terminals	Actuator Color	Housing Color
SWT	PLC	XX	XX	X	XX	XX
Switch	Push button, see drawing	11=SPST OFF-ON 12=SPST, OFF-MOM 21=DPST, OFF-ON 22=DPST, OFF-MOM	12=12VDC 24=24VDC 125=125VAC 250=250VAC	F=Faston Type	See Color Chart	WT=White BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/17/09
				Checked	Lizzy	04/17/09
				Drawn	Tina	04/17/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		



Central Components Manufacturing

440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SWT-PLC-XX-XX-F-XX-XX**

Description: Push button switch,