



SPECIFICATIONS

Electrical Rating: 16A 250VAC;
15A 125VAC
Contact Resistance: <20mΩ
Insulation Resistance: >1000MΩ 500VDC
Withstanding: >1500V/1-minute
Durability: 10000 cycles min.
Operating Temp: -25°C to +85°C

Code	Color
LYL	Yellow*
LGN	Green*
LBL	Blue*
LWT	White*
LRD	Red*

*Illuminated

Item	Name	Material	Finish
1	Rocker	PC	
2	Rocker Holder	PBT	
3	Housing	PA66	
4	Contact	AgCd012	
5	Actuator	Brass H62	
6	Contact	AgCd012	Silver
7	Terminal	Brass H62	Silver
8	Terminal	Brass H62	Silver
9	Spring	QSn6.5-01	Nickel
10	Spring	Spring Steel	
11	Lamp	Neon Lamp	

Series	Type	Version	Terminals	Actuator Color	Housing Color	Terminal Plating
SWT	R	20	F	XX	BK	N
Switch	Rocker	DPST ON/OFF	F=Faston Type	See Color Chart	BK=Black	N=Nickel

RoHS Compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/17/13
				Checked	Lizzy	09/17/13
				Drawn	Tina	09/17/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SWT-R-KCD2-20-F-LXX-BK-N**

Description: Rocker Switch, DPST with lighted actuator