



SPECIFICATIONS

Current Rating: 2.0 Amps
 Contact Material: Copper
 Contact Resistance: 20mΩ Max.
 Insulation Material: Polyester, UL94V-0, Nylon 6-T
 Insulation Resistance: 1000MΩ Min.
 Operating Temp: -40°C to +105°C

Recommended
 P.C.Board
 Hole Layout



Series	Rows	Positions	Tail Code	Plating
BPH	XX	XX	A	XX
2mm Receptacle Strip	01=Single 02=Double	02-40 Single 04-80 Double	A=2.4mm CS=Custom	TN=Tin SGXX=Selective Gold GDXX=Gold XX=10, 15, 30u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/20/05
				Checked	Lizzy	04/20/05
				Drawn	Tina	04/20/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-01-XX-A-XX**

Description: 2mm Through Hole Receptacle Strip, 4.3mm Profile