



P.C. Board Layout

SPECIFICATIONS

Insulator: Material: PBT & 30% Fiber(UL 94V-0)
 Contact Resistance: 30MΩ at CS 100MA
 Insulator Resistance: 1000MΩ Min at DC 250V
 Current Rating: 1 AMP
 Withstanding Voltage: AC 500V for 1 minute
 Temperature Rating: -40°C ~ +85°C
 Contact Material: Phospher Bronze
 Plating: Tin plated.

Dimensions				
PINS	A	B	C	D
6	7.62	5.08	9.96	7.62
8	10.16	7.62		
14	17.78	15.24		
16	20.32	17.78		
18	22.86	20.32		
20	25.4	22.86		
24	30.48	27.94	17.60	15.24
28	35.56	33.02		
24	30.48	27.94		
28	35.56	33.02		
32	40.64	38.1		
40	50.8	48.296		
42	53.34	50.80		

Series/Width	Positions	Plating	Options
CICX-B	XX	TN	XXX
IC Socket X: 3=.300" 6=.600"	CIC3:06,08,14,16,18,20,24,28 CIC6:24,28,32,40,42	TN=Tin	None if Blank OPN=Open Frame (CIC6)

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	8/10/99
				Checked	Lizzy	8/10/99
				Drawn	Tina	8/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CICX-B-XX-TN**

Description: IC Socket 2.54mm

