


SPECIFICATIONS
Voltage Rating: 125V RMS
Current Rating: 1.5A
Contacts: Phos Bronze Flat Pin,
T=0.30mm
Contact Plating: 50µm Gold
Contact Resist: 100 Milliohms max
Housing Material: PC UL 94V-0
Insulation Resist: 1000 Megohms
at 500 VDC min
PCB Material: FR-4, 1.6mm thick
Withstanding: 750 RMS/1 min.
Operating Temp: 0°C to +70°C

COLOR CODING INFORMATION			
T568B		T568A	
PIN 1	ORANGE/WHITE	PIN 1	GREEN/WHITE
PIN 2	ORANGE	PIN 2	GREEN
PIN 3	GREEN/WHITE	PIN 3	ORANGE/WHITE
PIN 4	BLUE	PIN 4	BLUE
PIN 5	BLUE/WHITE	PIN 5	BLUE/WHITE
PIN 6	GREEN	PIN 6	ORANGE
PIN 7	BROWN/WHITE	PIN 7	BROWN/WHITE
PIN 8	BROWN	PIN 8	BROWN

Category
XX
5E=Cat 5e
6=Cat 6
6A=Cat 6a



RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/31/15
				Checked	Lizzy	03/31/15
				Drawn	Tina	03/31/15
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CLC-8-08-KJ55-BK-P3-XX**

Description: Inline coupler UTP. Available as Cat 5e. Cat 6 and Cat 6a