



SPECIFICATIONS

Current Rating: 25A
 Voltage Rating: 300V
 Terminals: 0.8t, Tin Plated
 Housing: PA66, UL94V-0
 Screw: Steel, M4 Nickel Plated
 Insulation Resistance: 500MΩ/500VDC
 Withstanding: 2000VAC min.
 Wire Range: 22 to 12AWG
 Max Torque: 1.2N.m 10.6Lb In
 No. Of Contacts: 02-15
 Temperature Range: -40°C ~ +105°C

Series	Type/Options	Pitch	Positions	Color
CMTB	F2565XY	1100	XX	BK
Terminal block	X: C=Straight center pin S=Straight side pin R=Right angle TF=Center solder tab w/flange Y:C=Cover	1100=11.00mm See also 762=7.62mm 825=8.25mm 850=8.50mm 1000=10.00mm	02-15	BK=Black BL=Blue GN=Green GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/04/07
				Checked	Lizzy	06/04/07
				Drawn	Tina	06/04/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F2565-1100-XX-XX**

Description: 11.00mm pitch barrier strip