



SPECIFICATIONS

Current Rating: 25A
Voltage Rating: 300V
Terminals: 0.8t, Tin Plated
Housing: PA66, UL94V-0
Screw: Steel, M4 Nickel Plated
Insulation Resistance: 500MΩ/500VDC
Withstanding: 2000VAC min.
Wire Range: 22 to 12AWG
Max Torque: 1.2N.m 10.6Lb In
No. of Contacts: 02-15
Temperature Range: -40°C ~ +105°C

Series	Type/Options	Pitch	Positions	Color
CMTB	F2565XY	XXX	XX	BK
Terminal block	X: C=Straight center pin S=Straight side pin R=Right angle TF=Center solder tab w/flange Y:C=Cover	762=7.62mm 825=8.25mm 850=8.50mm See also 1000=10.00mm 1100=11.00mm	02-15	BK=Black BL=Blue GN=Green GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/04/07
				Checked	Lizzy	06/04/07
				Drawn	Tina	06/04/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F2565S-825-XX-XX**

Description: 8.25mm pitch barrier strip