



SPECIFICATIONS

Impedance: 75Ω
 Frequency Range: 0~11GHz
 Working Voltage: 170V max
 Withstanding: 500V rms
 VSWR
 Straight: ≤1.2
 Right Angle: ≤1.3
 Contact Resistance
 -Center Contact: ≤10mΩ
 -Outer Contact: ≤5mΩ
 Insulation Resistance: ≥5000MΩ
 Body: Brass, Nickel Plating
 Center Conductor: Phosphor Bronze, Silver Plated
 Coupling Nut: Brass, Nickel Plating
 Gasket: Silicone Rubber, Nickel Plating
 O-Ring Seal: 6146 Silastic
 Insulator: PTFE
 Temperature Range: -40C ~ +60C
 Durability: >500

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/16/12
				Checked	Lizzy	08/16/12
				Drawn	Tina	08/16/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm
						Central Components Manufacturing 440 Lincoln Blvd., Middlesex, New Jersey 08846 Phone 732 469-5720 888 288-5152 Fax 732 469-1919
						Part No.: CRF-ADT-2862-BNTS-B
						Description: F Connector Adapter Type 2862 75ohm, F Plug to F Plug Straight