


SPECIFICATIONS


Current Rating: 15 A DC
 Voltage Rating: 250 VAC, 350 VDC
 Material: Brass, 0.4 thick
 Plating: Tin 40µ" min.
 Thickness: 0.4
 Hardness: SH
 Insulation: OD 3.8 max.
 Operating Temp: -25C to +85C

Wire Range: 14 to 20 AWG
 Mating Pin: 0.8 Thick

Dimensions		
Item	Dim (mm)	Tolerance (±)
T	0.4	0.03
L	16.1	0.35
E	7.7	0.25
W	7.6	0.15
IS	5.1	0.25
WS	3.2	0.25
H	4.7	0.25
H1	3.2	0.32
H2	3.2	0.32

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/30/10
				Checked	Lizzy	08/30/10
				Drawn	Tina	08/30/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-2362BS-2**

Description: Fast on connector, female right angle